

## En D7500 Online Manual

## **Compatible Non-CPU Lenses**

Non-CPU lenses may only be used when the camera is in mode M. Selecting another mode disables the shutter release. Aperture must be adjusted manually via the lens aperture ring and the camera metering system, i-TTL flash control, and other features requiring a CPU lens can not be used. Some non-CPU lenses can not be used; see "Incompatible Accessories and Non-CPU lenses".

Camera setting	Focus mode			Shooting mode	
		MF (with electronic			
Lens/accessory	AF	rangefinder)	MF	M	Other modes
AI-, AI-modified NIKKOR or Nikon Series E lenses	_	<b>✓</b> 1	<b>V</b>	<b>✓</b> ²	_
Medical NIKKOR 120mm f/4	_	~	<b>V</b>	✓ 2,3	<u> </u>
Reflex NIKKOR	_	_	<b>V</b>	<b>√</b> 2	<u> </u>
PC NIKKOR	_	<b>✓</b> <sup>4</sup>	<b>V</b>	<b>✓</b> ²	T —
Al-type Teleconverter	_	<b>✓</b> 5	<b>V</b>	<b>✓</b> ²	<u> </u>
PB-6 Bellows Focusing Attachment <sup>6</sup>	_	<b>✓</b> 1	<b>V</b>	<b>√</b> 2	<u> </u>
Auto extension rings (PK-series 11A, 12, or 13; PN-11)	_	<b>✓</b> 1	~	<b>✓</b> 2	T -

- 1 With maximum aperture of f/5.6 or faster.
- 2 Exposure indicator can not be used.
- 3 Can be used at shutter speeds slower than flash sync speed by one step or more.
- 4 Can not be used with shifting or tilting.
- 5 With maximum effective aperture of f/5.6 or faster.
- 6 Attach in vertical orientation (can be used in horizontal orientation once attached).